



## APPLICATIONS

**Eni Grease CC 2** is a yellow anhydrous-calcium base grease, smooth-textured.

The calcic base gives good water washout resistance characteristics both in presence of hot or cold water.

**Eni Grease CC 2** can be applied by automated and manual pressure greaser for the lubrication of pins, bearings, guides and joints also exposed to the moisture, water action and subjected to thermal and mechanical not heavy stresses (speed and pressure).

## CUSTOMER ADVANTAGES

- Ensures a film on surfaces with good lubricating and protective characteristics.
- Water Repellent and insoluble both in hot or cold water

## SPECIFICATIONS & APPROVALS

- DIN 51825 K 2G -20
- ISO 12924 L-XBBGA 2





## CHARACTERISTICS

Properties	Method	Unit of Measure	Typical
Consistency (NLGI grade)	-	-	2
Thickener type	-	-	calcium anhydrous
Base oil type	-	-	mineral
Base oil viscosity at 40 °C	ASTM D 7042	mm <sup>2</sup> /s	100
Appearance	-	-	homogeneous
Colour	-	-	light amber
Drop point	ASTM D 566	°C	145
Penetration, worked, 60 d. s.	ASTM D 217	dmm	280
Water washout at 79°C	ASTM D 1264	% (m/m)	2
Temperature range	-	°C	-20/+80

## WARNINGS

- Not mix with different types of grease (thickener) to avoid incompatibility problems.

