



APPLICATIONS

Eni Mix 2T is a lubricant developed for 2-stroke engines of scooters and motorcycles, air- or liquid-cooled. According to the type of engine, the product can be manually mixed into fuel tank or used in the self mixing lubricating system.

CUSTOMER ADVANTAGES

- **Eni Mix 2T** is formulated using a low ash content additive package which minimizes combustion chamber deposits, spark-plug fouling and the blocking of exhaust ports. Its detergent properties minimize lacquer formation and carbon deposits thus preventing piston-ring sticking.
- **Eni Mix 2T** reduces rust and corrosion in the engine resulting from attack by combustion moisture and acids.

SPECIFICATIONS & APPROVALS

- API TC

CHARACTERISTICS

| Properties | Method | Unit of Measure | Typical |
|--------------------|-------------|--------------------|---------|
| Colour | - | - | red |
| Density at 15°C | ASTM D 4052 | kg/m ³ | 871 |
| Viscosity at 100°C | ASTM D 445 | mm ² /s | 9.0 |
| Viscosity at 40°C | ASTM D 445 | mm ² /s | 62 |
| Viscosity Index | ASTM D 2270 | - | 121 |
| Flash point P.M. | ASTM D 93 | °C | 111 |
| Pour point | ASTM D 97 | °C | -28 |

